

SERVICE MASTER® 1000

Article No.: 63210GT405

SERVICE MASTER®1000 Coverall is made of breathable microporous fabric with superior protection against hazardous liquid spray and fine particulates. Built with 3-piece hood, storm flap zipper closure, elastic backwaist, cuffs and ankles. Certified to CE Cat. III Type 5 & 6, EN1149 antistatic and protects against radioactive particles as per EN1073.2.



EN ISO 13982-1:2004
+A1:2010



EN 13034:2005
+A1:2009



EN 14126:2003
+AC:2004



EN 1073-2:2002




EN 1149-5:2008



- EN ISO 13034 (T6)
- EN ISO 13982 (T5)
- EN 14126
- EN 1073-2
- EN 1149-5
- CE CAT III



LOW LINT



EXCELLENT BARRIER PROTECTION

• A very effective in holding out dust particles and chemicals to meet with 5/6 standards - even better than its predecessor.

HIGHER COMFORT

• Is lighter and even more breathable than before and certainly the most comfortable 5/6 product on the market.

ENVIRONMENTALLY FRIENDLY

• Uses 20% less raw materials than any other product on the market whilst offering better barrier.

SERVICE MASTER® 1000 FEATURES

- ROBUST LIGHTWEIGHT PROTECTION
- EXCEPTIONAL LIQUID DEFENSE (Unique seam stitching)
- AEROSOL RESISTANT
- OUTSTANDING BREATHABILITY
- EXCEPTIONAL FIT (Greater ease of movement)
- ANTI-STATIC TREATMENT
- COMFORTABLE DESIGN
- SILICON-FREE
- ULTRA LOW LINTING



Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT CH 8036-3.2

GLYPTEC®
SERVICE MASTER® 1000
Article No.: 63210GT405

STYLE & COMPONENTS

1. 3-piece hood
2. 2-way #3 white nylon coil zipper
3. 1-ply stormflap with adhesive tape for secure fastening
4. Elasticated waist on back for a better fit
5. Breathable fabric
6. Elasticated cuffs
7. Elasticated ankles

PACKING

PACKING

WHITE

APPLICATIONS

- Industrial & Petrochemical
- Agriculture & Farm Pesticide
- Abattoirs
- Asbestos Handling
- Car Industry
- Clean Room Farming
- Food Processing Industry
- Maintenance and Repairs
- Medical / Emergency Services
- Pharmaceutical
- Police - Scene of Crime
- Forensic Science
- Technology Industry
- 2-Pack Paint Spray
- Waste Management Services

SIZE CHART

	HEIGHT	
	S	164-170cm (5'4" - 5'6")
	M	167-176cm (5'5" - 5'9")
	L	174-181cm (5'8" - 6')
	XL	179-187cm (5'11" - 6'2")
	2XL	186-194cm (6'1" - 6'4")
	3XL	194-200cm (6'3" - 6'6")
	CHEST	
S	84-92cm (33" - 36")	
M	92-100cm (36" - 39")	
L	100-108cm (39" - 42")	
XL	108-115cm (42" - 45")	
2XL	115-124cm (45" - 49")	
3XL	124-132cm (49" - 52")	

DONNING / DOFFING


Performance of Glyptec® Service Master® 1000	Test Method	Index of penetration	Index of repellency
Resistance to 30% Sulphuric Acid	EN 6530	3/3	3/3
Resistance to 10% Sodium Hydroxide	EN 6530	3/3	3/3
Resistance to o-Xylene	EN 6530	3/3	2/3
Resistance to Butan-1-ol	EN 6530	3/3	3/3

Physical Data	Test Method	Class Result
Whole Suit Dust Test (Type 5)	EN 13982-1/04	Pass
Light Spray Test (Type 6)	EN 468 (EN13034+EN17491-4)	Pass
Abrasion Resistance	EN 530 Method 2	3/6
Trapezoid Tear Resistance	EN ISO 9073-4:1999	2/6
Seam Strength	BS EN ISO 13935-2:2001	3/6
Flex Cracking Resistance	ISO 7854 Method B	6/6
Puncture Resistance	EN 863	2/6
Inward Leakage		Pass - Ljmn 82/90 ≤ 30% LS 8/10 ≤ 15%
Tensile Strength	ISO 13934-1:2000	2/6
Protection Against Radioactive Contamination	EN 1073-2:2002	1/6
Anti-static	EN 1149-5:2008	Pass

Doc. Control:	Rev.: 3.2	Date: April 9, 2016
---------------	-----------	---------------------

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT CH 8036-3.2



A PRODUCT OF

